




EQUIPMENT	Less than 16 feet	16 to less than 26 feet	26 to less than 40 feet	40 to not more than 65 feet
BACKFIRE FLAME CONTROL	One approved device on each carburetor of all inboard gasoline engines.			
SOUND-PRODUCING DEVICE 	Some means of making an efficient sound signal audible for 1/2-mile. A whistle or horn must be readily accessible to the operator of boat or passengers. An athletic coach's whistle is acceptable.		Must carry a sound signal audible for 1/2-mile.	
PORTABLE FIRE EXTINGUISHER WHEN REQUIRED 	At least one B-I or 5-B portable fire extinguisher.	At least two B-I or 5-B portable fire extinguishers or one B-II or 20-B	At least three B-I or 5-B portable fire extinguishers or one B-I/5-B and one B-II/20-B.	
NAVIGATION LIGHTS	Must comply with Inland Navigation Rules and state regulations.			
MUFFLING DEVICE	Efficient muffling device required to prevent excessive or unusual noise.			
LIFE JACKETS (PFDs AND THROWABLE DEVICES) (page 6) 	One USCG-approved wearable life jacket for each person on board. Must be used in accordance with the requirement on the approval label.	One USCG-approved wearable life jacket on board for each person and, in addition, one throwable device must be used in accordance with the requirements on the approval label. Canoes, kayaks, and paddleboards, regardless of length, are not required to carry a throwable device.		
VENTILATION	Boats with closed compartments or permanently installed fuel tanks must be equipped with an efficient natural or mechanical bilge ventilator or meet the applicable Coast Guard construction standards for fuel and electrical systems.			