



CHANNEL BLOCK WITH LOG FRAME

Plan View



Section View




Note: Channel block built lower than surrounding streambanks while maintaining normal water level height
Maximum device height is 3/4 to the top of the bank




CHANNEL BLOCK WITH ROOTWADS

Plan View



Section View




Note: Channel block built lower than surrounding streambanks while maintaining normal water level height
Maximum device height is 3/4 to the top of the bank




CHANNEL BLOCK WITH SINGLE LOGS AND ROOTWADS

Plan View



Section View




Note: Channel block built lower than surrounding streambanks while maintaining normal water level height
Maximum device height is 3/4 to the top of the bank




CHANNEL BLOCK WITH STONE

Plan View



Section View




Note: Channel block built lower than surrounding streambanks while maintaining normal water level height
Maximum device height is 3/4 to the top of the bank




BRUSH DEFLECTOR (LOW GRADIENT STRUCTURE)

Plan View



Section View



Note: Christmas tree/brush bundles attached to stakes and to other bundles with natural fiber twine
Stakes must be made of wood or other natural material


Note: Recommended only for use in low gradient systems

DHM, PFBC 2022




LOG FACED STONE DEFLECTOR

Plan View



Section View




- Sill Logs = 10-15'
- Face Logs = 20'
- Frame Log = 20-30'
- Log Dia. = 8-12"




LOG FRAMED DEFLECTOR WITH BOARDS

Plan View




Note: Sections can be added or removed
Each section includes two sill logs and two face logs

Section View



Oak planking nailed into the top of the back log and buried into streambank



Note: Front face log kept higher to protect edge of oak planks


- Sill Logs = 10-15'
- Face Logs = 20'
- Frame Logs = 20'-30'
- Log Dia. = 8-12"

Frame log buried in trench with rock




LOG FRAMED STONE DEFLECTOR

Plan View



Note: Sections can be added or removed
Each section includes two sill logs and two face logs

Section View




- Sill Logs = 10-15'
- Face Logs = 20'
- Log Dia. = 8-12"



OPEN CENTER STONE DEFLECTOR WITH LOGS


(LOW GRADIENT STRUCTURE)

Plan View



Note: Length measurement is 2.5 times the width
Deflector sizes may vary

Section View



Log Length = 15-25'

Log Dia. = 8-12"


Note: Recommended only for use in low gradient systems

DHM, PFBC 2022




RANDOM BOULDER PLACEMENT

Plan View



Note: Place boulders in the middle third of the wetted width of the stream to prevent flow deflection into the streambanks

Section View




Note: Boulder should be large enough not to be displaced during high flow periods
Boulder height should be within 2" of normal water level




ROOTWAD DEFLECTOR

Plan View



Note: Can be placed as a single deflector or overlapping as shown

Section View




Rootwad Dia. = 3-6'
Rootwad Length = 10-15'




SAWTOOTH STONE DEFLECTORS WITH LOGS

Plan View



Note: Logs should be protruding 2 to 3 feet from rock face

Section View



Log Length = 10-15'


Log Dia. = 8-12"

DHM, PFBC 2022




SAWTOOTH STONE DEFLECTORS

Plan View




Note: Sections can be added or removed and the length measurement is 2.5 times the width


Section View



STONE DEFLECTOR WITH ROOTWADS




Note: Length measurement is 2.5 times the width
Deflector sizes may vary




Rootwad Dia. = 3-6'
Rootwad Length = 10-15'



STONE DEFLECTOR WITH SINGLE LOG AND J-HOOK




Note: Length measurement is 2.5 times the width
Deflector sizes may vary




Log Length = 15-25'
Log Dia. = 8-12"



STONE DEFLECTOR WITH SINGLE LOG



Note: Length measurement is 2.5 times the width
Deflector sizes may vary




Log Length = 15-25'

Log Dia. = 8-12"


DHM, PFBC 2022



STONE DEFLECTOR




Note: Length measurement is 2.5 times the width
Deflector sizes may vary



LARGE WOOD DEVICES


Plan View



Note: Trees should be large enough and have enough ballast to prevent movement during high flow periods

Note: When possible trees should be "pinned" between stumps and or living trees to reduce likelihood of movement

Section View




Trees = minimum 10" dia.

DHM, PFBC 2022




BANK COVER CRIBBING WITH ROOTWADS

Plan View



Section View




Rootwad Length = 10-15'
 Face Logs = 20'
 Log Dia. = 8-12"




BANK COVER CRIBBING

Plan View




2' Rebar



Note: Front face log kept higher
to protect edge of oak planks

Section View



Sill Logs = 10-15'


Face Logs = 20'

Log Dia. = 8-12"



BRUSH REVETMENT


Plan View



Note: Sill logs should be placed every 15-20 ft and attached to other trees using rebar if necessary
Stone can be added on top of the brush/trees for structural integrity/ballast

Section View

Note: 2' or 4' rebar connecting brush/trees together to the sill logs




Note: Structure material should not exceed bankfull height


DHM, PFBC 2022



MODIFIED MUD SILL CRIBBING WITH ROOTWADS



Note: Each section includes two rootwads and at least two face logs, sections can be added or removed




Rootwad Length = 10-15'
 Face Logs = 20'
 Log Dia. = 8-12"

DHM, PFBC 2022



MODIFIED MUD SILL CRIBBING


Plan View



Note: Each section includes two sill logs and at least two face logs, sections can be added or removed

Note: Ending section can have extended sill log

Section View




Sill Logs = 10-15'
 Face Logs = 20'
 Log Dia. = 8-12"




MUD SILL CRIBBING

Plan View



Note: Mud sill cribbing constructed in 8' sections
Sections can be added or removed

Section View




Sill Logs = 10-15'
Face Logs = 8'
Log Dia. = 8-12"

DHM, PFBC 2022




SAWTOOTH MODIFIED MUDSILL CRIBBING

Plan View



Note: Each section includes two sill logs and two face logs
Sections can be added or removed

Section View




Sill Logs = 10-15'
Face Logs = 20'
Log Dia. = 8-12"




TOE LOG CRIBBING

(LOW GRADIENT STRUCTURE)

Plan View



Section View



Log Dia.= 8-12"


Note: Recommended only for use in low gradient systems

DHM, PFBC 2022




CROSS LOG VANE

(LOW GRADIENT STRUCTURE)



4' Rebar Pin

Section View



Log Length = 15-25'

Log Dia. = 8-12"


Note: Low gradient structure designed to prevent gravel bar growth

DHM, PFBC 2022




LOG CROSS VANE WITH ROCK THROAT

Plan View



Section View




Log Length = 10-25'
Log Dia. = 8-12"




LOG CROSS VANE (LOW GRADIENT STRUCTURE)

Plan View



Section View



Log Length = 10-25'

Log Dia. = 8-12"


Note: Recommended only for use in low gradient systems

4' Rebar




LOG FRAMED CROSS VANE WITH ROCK THROAT

Plan View



Note: Sections can be added or removed

Section View




Sill Logs = 10-15'
 Face Logs = 20'
 Frame Logs = 20-30'
 Log Dia. = 8-12"

DHM, PFBC 2022




LOG FRAMED CROSS VANE

Profile View




Note: Upstream wings can be log or stone
 Note: Additional upstream or downstream wing sections can be added




Note: Excavated trench in stream bottom
 3' deep x 6' sloped x width of the stream

Plan View



Section View




Sill Logs = 10-15'
 Face Logs = 20'
 Cross Logs = 10-30'
 Log Dia. = 8-12"




LOG FRAMED CROSS VANE WITH WING EXTENSIONS

Profile View




Note: Upstream wings can be log or stone
 Note: Additional upstream or downstream wing sections can be added




Note: Excavated trench in stream bottom
 3' deep x 6' sloped x width of the stream

Plan View



Section View




Sill Logs = 10-15'
 Face Logs = 20'
 Cross Logs = 10-30'
 Log Dia. = 8-12"




MULTI-LOG VANE DEFLECTOR WITH J-HOOK

Plan View




Section View




MULTI-LOG VANE DEFLECTOR

Plan View




Section View





ROCK CROSS VANE

Plan View



Streambank graded to a 3:1 slope


Section View




ROCK RIFFLE

(LOW GRADIENT STRUCTURE)

Plan View



Section View




Note: Recommended only for use in low gradient systems

DHM, PFBC 2022




ROCK VANE DEFLECTOR

Plan View





Section View




ROCK VANE DEFLECTOR WITH J-HOOK


Plan View



Section View





SINGLE LOG VANE DEFLECTOR WITH J-HOOK AND ROOTWAD




SINGLE LOG VANE DEFLECTOR WITH J-HOOK

Plan View




Section View




SINGLE LOG VANE DEFLECTOR

Plan View



4' Rebar Pin

Section View



Log Length = 15-25'

Log Dia. = 8-12"

DHM, PFBC 2022

